



Specs	
Fs	24.1 Hz
Qms	5.63
Vas	1.8 cu.ft 49.8 Liters
Cms	0.126 mm / N
Mmd	12 oz. 340 Grams
Xmax	0.63 in. 17 mm
Qes	0.45
Re	2.0 ohms
Z	2.0 ohms
BL	16.1 Telsa / m
Pe	1600 Watts
Qts	0.41
SPL	89.4 dB
V.C.	3 in. dia. 75 mm

COMP X212

Total Volume: 0.9 cu. Ft.
F3: 42 Hz
Acceptable Box Sizes: 8 - 1.0 cu. Ft.




Total Volume: 1.5 cu. Ft.
Port Diameter: 4 in.
Port Length: 15.4 in.
Fb: 35 Hz
F3: 26 Hz



Specs	
Fs	23.5 Hz
Qms	7.33
Vas	4.2 cu.ft 119 Liters
Cms	0.123 mm / N
Mmd	12.7 oz. 360 grams
Xmax	1.10 in. 28 mm
Qes	0.56
Re	2.0 Ohms
Z	2.0 ohms
BL	14.0 Telsa / m
Pe	1600 Watts
Qts	0.52
SPL	92.2 dB
V.C.	3 in. dia. 75 mm

COMP X215

Total Volume: 2.0 cu. Ft.
F3: 41 Hz
Acceptable Box Sizes: 1.8 - 2.2 cu. Ft.



Total Volume: 3.0 cu. Ft.
Port Diameter: 4 in.
Port Length: 13.5 in.
Fb: 26 Hz
F3: 25 Hz

